



**Putzmeister**

## Your benefits

- Infinitely adjustable delivery rate
- Large hopper ideal for filling from truck mixers
- Integral 120 bar high-pressure cleaner
- Large toolbox (100 l)
- Central, easily adjustable support leg with low drawbar load
- Grille with vibrator for improved material flow
- Excellent soundproofing due to sound insulated engine
- Easy access makes all parts easy to service
- Extremely lightweight, impact resistant plastic hood
- CE conformity meets all safety standards in the EU
- Made in Germany

## SP 11 THF – Convenient, economical placement of self levelling floor screed



The SP 11 THF can easily cover distances of 100 m or heights of 60 m. The grille and vibrator have been improved to achieve a continuous material flow, even when conveying screed containing plastic or metal fibres. The maximum delivery rate of 15 m<sup>3</sup>/h and the installed equipment provide all you need to professionally convey self levelling floor screed. Wear and maintenance parts are easy to access, which makes cleaning and the replacement of wear parts more convenient. You can therefore reduce setup times and increase working productivity.

For further information related to technical details or application, please contact your local Putzmeister dealer.

- **Calcium sulphate screed** (anhydrite)
- **Cement floor screed**





The extremely powerful and reliable Kubota 4-cylinder engine promises impressively low operating costs and operates extremely quiet due to improved sound insulation.



The grille and the enhanced vibrator ensure reliable, continuous material flow for an efficient pumping performance.



The large toolbox provides enough space for e.g. a spray lance, tools, spare parts, water hose and many other accessories.

## Technical data

## SP 11 THF

<b>Feed hopper</b>	220 l
<b>Pump</b>	Worm pump 2L75
<b>Delivery rate*</b>	0-15 m <sup>3</sup> /h (250 l/min)
<b>Delivery pressure</b>	20 bar
<b>Delivery range**</b>	100 m horizontal, 60 m vertical
<b>Engine</b>	4-cylinder Kubota diesel; 22.7 kW at 2,600 rpm
<b>Weight (fully fuelled)</b>	under 750 kg
<b>Length × width × height</b>	3,260 × 1,420 × 1,160 mm
<b>Filling height</b>	1,000 mm
<b>Maximum particle size</b>	8 mm
<b>Chassis</b>	unbraked, suitable for road use

\* The delivery rate is theoretical and depends on the pump pressure.

\*\* The data is based on experience and depends on the material properties.

## Equipment

Car cable adapter	■
Car coupling	■
Cleaning tool	■
Cover grille MW 15	■
Grease cartridge	■
High-pressure cleaner	■
Instruction manual and spare parts list	■
Lever press with hose	■
Seal ring for mortar coupling	■
Standard colour paintwork	■
Standard tool	■
Vibrator	■
Cable remote control	□
Radio remote control	□
Radio remote control with adjustable delivery rate	□
Screen grille MW 10	□
Special canopy paint in RAL colours	□
Support wheel	□
Truck coupling	□
Working lights	□

□ Optional    ■ Standard

## Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany  
 P.O.Box 2152 · 72629 Aichtal / Germany  
 Tel. +49 7127 599-0 · Fax +49 7127 599-743  
 mm@pmw.de · www.pmmortar.de

